





## Superlight Nano 2

8 818 055 059

4 × 1,7 W, 580 lm, 4000 K neutral white,  
wide beam 31°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of die-cast aluminum ALSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, powder coated die cast zinc mounting bracket with tilt scale: 2 drilled holes  $\varnothing$  7 mm, spacing 50 mm, 1 centre hole  $\varnothing$  11 mm, tilt range: 120°, cable gland: M20, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 31°, luminous flux: 580 lm, wattage: 7 W, delivered lumens 83 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,008 m<sup>2</sup>, dimensions (L×H×W): 76 × 85 × 76 mm, weight 0.9 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP67 IK08

## Specification

|                            |                      |                             |                         |
|----------------------------|----------------------|-----------------------------|-------------------------|
| Wattage                    | 7 W                  | Beam angle (FWHM)           | 31°                     |
| Delivered lumens           | 83 lm/W              | Housing colour              | silver grey             |
| Light source               | LED 4000 K           | Power supply cable          | $\varnothing$ 6 – 13 mm |
| Color Rendering Index      | CRI > 80             | Protection type             | IP67                    |
| Colour tolerance           | max 2 SDCM           | Protection class            | I                       |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Impact resistance           | IK08                    |
| Control gear               | on / off             | Windage area                | 0,008m <sup>2</sup>     |
| Input voltage AC           | 100 – 265 V          | Dimensions                  | 76 × 85 × 76 mm         |
| Input voltage DC           | 135 – 265 V          | Weight                      | 0,90 kg                 |
| Voltage protection         | 2 kV L/N   2 kV L/PE | Max. ambient temperature ta | 35°                     |
| Luminaires per B16A / C16A | 100 / 0              |                             |                         |